



PURE PLayer!









The new design of the Pro Open Range is firmly focused on adventure boating/ different way to live the sea, while providing a perfect balance of performance and comfort.

With excellent sea keeping qualities thanks to Zodiac®' Nautic deep V-shaped hull and optimized deck plan, the Pro Open provides exceptional ride quality and comfort.

The perfect ergonomics, easy maneuvering aboard, new aft bench seat on the 550 model: versatility of the Pro Open range has been designed in every detail in order to give you the possibility to live unique sensations and your sport passion without any limit. Its design allows to be easily transportable, even with the inflated tubes, and to fit your passions: getaways, fishing, water skiing, wake boarding, sunbathing...

The Pro Open allows you to share your passion for boating with your friends and family in style and comfort.

So start now!

The Points of the PRO OPEN

Special Technical Features

- Deep V-shaped hull
- Removable buoyancy tubes that are Zodiac patented

On-board Comfort

- Ease of movement
- Self-draining deck
- Tilt steering / overhead console with storage area
- 54 litre cooler on the Pro Open 650
- 75 litre fuel tank (Pro Open 550) or 120 litre fuel tank (Pro Open 650)
- Navigation lights
- Bathing ladder

lovelties

- New grey and black colours for the removable buoyancy tubes
- New three-places aft bench seat is standard on the Pro Open 550

The Pro Open 550 has a brand new aft bench seat can accommodate three passengers for improved comfort when boating in all sea conditions.

The adjustable/reclinable central seat provides the ability to install a ski mast or fold down the engine a wink/ in a blink of an eye/ in a flash/ simply and quickly/ at a glance.











24°



	PRO OPEN 550	PRO OPEN 650	
DIMENSIONS (metres - feet/inches)			
Overall length	5,5 - 18'1"	6,5 - 21'4"	
Inside length	3,35 - 10'12"	4,95 - 16'3"	
Overall width	2,5 - 8'2"	2,5 - 8'2"	
Inside width	1,35 - 4'5"	1,35 - 4'5"	
CAPACITY			
Number of Passengers (ISO) Cat B/C	11	5 / 13	
Total weight (kg - lbs)	440 - 970	670 - 1477	
DESIGN CATEGORY			
European directive N° 94/25/CE	С	B / C	
MOTORISATION			
Shaft: ● Short ■ Long ★ Extra long ★ Ultra long		mono 🗙	bi 🔣
Maximum power allowed ² (in Hp - kW)	90 - 67	150 - 112	-
Maximum power allowed ³ (in Hp - kW)	120 - 90	175 - 131	2 x 80 - 2 x 59
Maximum speed⁵ (in km/h - knots)	72 - 45	77 - 48	

Indicated measurements may vary by +f- 5% for weight and speed measurements. (1) Maximum permitted load is calculated using ISO standards. Caution is advised when operating fully laden basts. (2) Recommended power is based on optimal use of the boat's abilities under average load. Depending on use, choose either maximum (waterskiing) or minimum power (fishing, crusing), (3) The manufacturer's plate speedifies maximum allowed power. The power of your boat must not exceed this under any circumstances. (4) Maximum speeds are intended as a guide only, they were measured in ideal conditions by professional pilots with one person aboard. They may vary according to the engine manufacturer's catalogue, boat load, propeller type and water conditions. (6) Models in this catalogue are sometimes shown with optional accessories. Please check standard equipment supplied with each model and see your distributor for any additional equipment. Zodiac® Nautic continually strives to improve the quality of its products and as such reserves the right to modify or delete any model presented in this catalogue without prior notice.

Zodiac® Nautic recommends to wear a life jacket at all times; it is your own responsibility to check the legal obligations on your navigation zone.

EQUIPMENT

HULL

Hull angle

- · Deep V-shaped polyester hull
- Moulded non-slip deck
- · Self-draining cockpit
- 1 bow ring
- 1 bow mooring post
- · 2 stern mooring cleats
- · Central hold
- Bow locker divided into two compartments: Anchor locker
- + removable storage bin
- · 2 stern lockers
- · 2 bailers

TUBE

- Removable buoyancy tube
- Strongan[™] 1100 décitex fabric (on the Pro Open 550 PVC model)

- Hypalon[™]-Neoprene[™] 1670 décitex fabric on the Pro Open 550 NEO and on the Pro Open 650 NEO
- Polyester bow roller
- "Easy Push" valves
- Lateral lifelines
- 4 external handles
- · Ultra-wide anti-chafing deflector strip
- Short cones

STANDARD EQUIPMENT

- Reclining steering console cylinder with: Steering wheel
- + steering unit
- + cable (550)
- Hydraulic steering (650)
- Pilot's and co-pilot's bolster equipped with:
 - Footrest

- Handrail
- 4 fishing rod holders
- Storage box
- Windscreen
- · Stainless steel handrail
- Console doors
- · Navigation lights
- Fitted fuel tank with gauge (75 litres on the Pro Open 550/ 120 litres on the Pro Open 650)
 - + water/fuel separator
- Bathing ladder
- Bilge pump
- Battery cut-off switch
- 2 paddles
- Foot pump
- 1 repair kit
- · Owner's manual

EQUIPMENT SPECIFIC TO 550

24°

 3 aft passenger seats with adjustable central seat

EQUIPMENT SPECIFIC TO 650

- Upholstered cooler seat (54 litres capacity)
- Aft seating with removable backrest

OPTIONAL EQUIPMENT

- Removable backrest for bolster
- Bimini top
- Sundeck
- Ski mast
- Mooring awning

For more information, visit